

**Verpackungsmöglichkeiten:**

100 St. = 10 x 10er Faltschachteln

Packing options:

100 pcs. = 10 boxes of 10 pieces

Bemessungswerte / Ratings

Art.- No.	Strom Current	Spannung Voltage	Ausschaltvermögen Breaking capacity	Schmelzintegral [A ² s]	Verlustleistung power dissipation [W]
1038.118	1,25 A	660 V	160 kA	0,28	0,9
1038.119	1,5 A	660 V	160 kA	0,36	1,25
1038.120	2 A	660 V	160 kA	0,57	1,5
1038.121	2,5 A	660 V	160 kA	1,3	2
1038.122	3 A	660 V	160 kA	2,7	2,1
1038.123	4 A	660 V	160 kA	4,6	2,3
1038.124	5 A	660 V	160 kA	12	2,6
1038.125	6A	660 V	160 kA	25	2,7
1038.126	8 A	660 V	160 kA	44	2,9
1038.127	10 A	660 V	160 kA	33	2,4
1038.128	12,5 A	660 V	160 kA	55	3,4
1038.130	16 A	660 V	160 kA	82	3,4
1038.131	20 A	660 V	160 kA	145	4,1
1038.132	25 A	660 V	160 kA	250	4,3
1038.133	30 A	660 V	160 kA	470	4,7
1038.134	32 A	660 V	160 kA	740	5