



ISO9001  CE RoHS

## ER17335

**3.6v Primary Lithium Thionyl  
Chloride High Energy  
2/3A-size Bobbin Battery**

### Benefits

- High energy density
- High voltage, stable during most of the application's lifetime
- Wide range of operating temperature[-55°C~+85°C ]
- Low self-discharge rate  
[less than 1% per year of storage]
- Long storage life  
[ 10 years under normal room temperature]

### Main application

- Intelligent Instrument and meter
- Memory and standby power
- Alarms and security devices
- Automotive electronics
- Electronic toll collection
- Military devices

### Electrical characteristics (23±2°C)

Nominal capacity	2.1Ah
Nominal voltage	3.6V
Maximum recommended continuous current	100mA
Maximum recommended pulse current	200mA
Operating temperature range	-55°C~+85°C

 U.L. Component Recognition MH 29130

### Physical characteristics

Diameter[max]	17.0mm
Height[max]	33.5mm
Typical weight	18g

### Available terminations

S: Standard termination

T: Solder tabs

P: Axial pins

Special termination are available upon request.

MSDS is available upon request.


*Customer's Satisfaction  
Always Be Our Goal*



ISO9001 CE RoHS

# ER 17335




3.6v Primary Lithium Thionyl Chloride High Energy  
2/3A-size Bobbin Battery



S: Standard termination

## Warning:

- Fire, explosion and burn hazard.
- Do not recharge, short circuit, crush, disassemble, heat above 100°C incinerate.
- Do not use the battery beyond permitted temperature range.



## Wuhan Voltec Energy Sources Co.,Ltd.

Add: Wuhan zhongyuanChangjiang Scientific Tecnology park,  
Nansan Road, Hannan Economy Dev.zone, Wuhan  
Tel: +86-27-84732152 84732116  
Fax: +86-84662179

Website: [www.voltec-sunmoon.com](http://www.voltec-sunmoon.com)  
E-mail: [sunmoon@voltec-sunmoon.com](mailto:sunmoon@voltec-sunmoon.com)