DATASHEET - CYL FUSE 63A 500V 14X51 CYL GG PV14



Fuse-link, LV, 63 A, AC 500 V, 14 x 51 mm, gL/gG, IEC



Part no. Catalog No. CYL FUSE 63A 500V 14X51 CYL GG PV14 C14G63

EL-Nummer (Norway)

1600201

Delivery program

Don'tory program			
Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	Α	63
Rated voltage			AC 500 V
Size			14 x 51 mm
Utilization category			gL/gG
usable for size/applications			Photovoltaic for industrial applications for general purpose use
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])					
Size			14x51 mm		
Rated voltage		V	500 - 500		
Rated voltage			Other		
Voltage type			AC		
Utilization category			gL/gG (cable protection/equipment protection)		
Rated operating frequency		Hz	45 - 62		
Nominal current		Α	63		
With striker			No		
Release characteristic			Other		
Breaking capacity		kA	80		