

SPECIFICATIONS

Capacitance Range (uf/mfd)	30/5	35/7.5
	35/5	40/7.5
	40/5	5/7.5
	45/5	50/7.5
	50/5	55/7.5
	55/5	60/7.5
	60/5	70/7.5
	70/5	80/7.5
	80/5	
Maximum Voltage	370-440	
Frequency	50/60 Hz	
Temperature Range	-40 to +85°C	
Tolerance	+/-5%	
PCBs	No	
Format	Round	
Construction	Aluminum w/ Steel Cap	
Terminal Type	1/4 in. Quadruple QCT	
Terminals Per Post	4	
Agency Approvals	UL and CUL Listed	
	10,000 AFC Protected	
Warranty:	1 Year	
Product Features	<ul style="list-style-type: none"> - For use with 1 and 3 phase motors - Always in stock - Same Day Shipping! - Heavy duty aluminum casing with steel cap - No PCBs 	



Product Description

TEMCo's AC Electric Motor Dual Run Capacitors are designed specifically for replacement of OEM single and three phase motor capacitors. They are also suited for use in air conditioners. These units are housed in aluminum casing with a steel cap. All units are PCB-free. Units are always in stock and ship Fast with Same Day Shipping from California.

DIMENSIONS Dimensions in inches.

TEMCO ID	uf (mfd)	H	B	D
RC0138	30/5	3.75	1.96	2.08
RC0102	35/5	4.6	1.96	2.08
RC0108	40/5	5.2	1.96	2.08
RC0114	45/5	5.2	1.96	2.08
RC0120	50/5	5.4	1.96	2.08
RC0156	55/5	4.94	2.16	2.26
RC0126	60/5	5.2	2.35	2.48
RC0132	70/5	5.4	2.35	2.48
RC0162	80/5	5.14	2.36	2.48
RC0168	35/7.5	4.74	1.97	2.07
RC0174	40/7.5	4.74	1.97	2.07
RC0180	45/7.5	4.94	1.97	2.07
RC0144	50/7.5	5.49	1.96	2.08
RC0186	55/7.5	4.94	2.16	2.26
RC0192	60/7.5	4.94	2.16	2.26
RC0198	70/7.5	4.98	2.36	2.47
RC0204	80/7.5	5.14	2.36	2.48

