

Product characteristics

Inductive sensor

Plastic housing Ø 34 mm

Cable

Sensing range 30 mm; [nf] non-flush mountable

Electrical data

Electrical design

Operating voltage [V]

Protection class

Reverse polarity protection

Outputs

Output function

Voltage drop [V]

Minimum load current [mA]

Leakage current [mA]

Current rating

- Current rating (continuous) [mA]

- Current rating (peak) [mA]

Short-circuit proof

Overload protection

Switching frequency [Hz]

Monitoring range

Sensing range [mm]

Real sensing range (Sr) [mm]

Operating distance [mm]

Accuracy / deviations

Correction factors

Hysteresis [% of Sr]

Switch-point drift [% of Sr]

Environment

Ambient temperature [°C]

Protection

Tests / approvals

EMC

MTTF [Years]

Mechanical data

Mounting

Housing materials

Weight [kg]

Displays / operating elements

Output status indication

	AC/DC
	20...250 AC/DC
	II
	no
	normally open
	< 6.5 AC / < 6 DC
	5
	< 2.5 (250 V AC) / < 1.3 (110 V AC) / < 0.8 (24 V DC)
	250 AC / 100 DC; 350 AC (...50 °C)
	î: 2.2 A (20 ms / 0.5 Hz)
	no
	no
	25 AC / 50 DC
	30
	30 ± 10 %
	0...24.3
	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / aluminium approx. 0.3 / copper approx. 0.2
	1...15
	-10...10
	-25...80
	IP 67
	EN 60947-5-2
	EN 55011: class B
	607
	non-flush mountable
	PBT
	0.257
	yellow

IB0026 - Inductive sensor - eclass: 27270101 / 27-27-01-01

Electrical connection

Connection


PVC cable / 2 m; 2 x 0.5 mm²

Wiring

Core colors

BN brown

BU blue



Note: miniature fuse to IEC60127-2 sheet 1,
 ≤ 2 A (fast acting)

Accessories

Accessories (included)

Mounting clamp

Remarks

Remarks

Recommendation: check the unit for reliable function after a short circuit.

Pack quantity

[piece]

1