



PLUG-IN RELAY COMPACT UNIT AC 230,
2 CO CONTACT LED MODULE RED STANDARD PLUG-IN
SOCKET SCREW TERMINAL

General technical details:

Supply voltage frequency / for auxiliary and control current circuit / rated value

• minimum	Hz	50
• maximum	Hz	60

type of voltage

AC

Control supply voltage

• at 50 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230
• at 60 Hz / at AC / rated value		
• minimum	V	230
• maximum	V	230

Number of NC contacts

• for auxiliary contacts	0
--------------------------	---

Number of NO contacts

• for auxiliary contacts	0
--------------------------	---

Number of change-over switches

• for auxiliary contacts	2
--------------------------	---

Operating current / of the auxiliary contacts

• at AC-15	
------------	--

• at 230 V	A	2.5
Design of the switching function		changeover switch
• guided		No
Switching behaviour		monostable

Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		Yes
Width	mm	15.5
Height	mm	71
Depth	mm	78

Certificates/approvals:

General Product Approval

other



GOST

[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZS:RT4A4T30/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:RT4A4T30

last change:

Oct 24, 2011