### MINI MAGLITE® AA FLASHLIGHTS

•Features a candle mode for hands-free use •Includes a spare bulb in the end cap, and two alkaline AA hatteries

Part No.	Description
M2A016	Hang pack – black
M2A036	Hang pack – red
M2A116	Hang pack – blue
M2A026	Hang pack – camouflage
M2A01L	Presentation box – black
M2A03L	Presentation box – red
M2A11L	Presentation box – blue
M2A02L	Presentation box – camouflage
M2A01H	Flashlight with holster - hang pack - black
M2A03H	Flashlight with holster – hang pack – red
M2A11H	Flashlight with holster – hang pack – blue
M2A02H	Flashlight with holster – hang pack – camouflage
AM2A056	Nylon full flap holster – hang pack – black
AM2A016	Accessory pack with pocket clip, wrist strap with key ring, lens holder; red, clear, and amber lenses – hang pack
LM2A001	Card of 2. Mini Maglite AA bulbs











#### MAG-NUM STAR® XENON REPLACEMENT LAMP "RETRO-FIT KIT

•For C or D Maglite Incandescent Flashlights •New high performance bi-pin style lamp, higher lumen output and improved beam quality •Retro-Fit kit includes lamp, lamp adapter, and retainer collar

	Description
LMXA201	For 2 cell C or D
	For 3 cell C or D
	For 4 cell C or D
	For 5 cell C or D
LMXA601	For 6 cell C or D



LMXA201

# MAGLITE® C & D CELL FLASHLIGHTS

·Includes a spare White Star® krypton bulb in the end cap •Hang pack

Dort No Doc

Part No.	Description		
S2C016	2 C cell flashlight - black		
S3C016	3 C cell flashlight – black		
S2D016	2 D cell flashlight – black		
S2D036	2 D cell flashlight - red		
S2D116	2 D cell flashlight - blue		
S3D016	3 D cell flashlight – black		
S3D036	3 D cell flashlight – red		
S3D116	3 D cell flashlight – blue		
S4D016	4 D cell flashlight – black		
S4D036	4 D cell flashlight – red		
S5D016	5 D cell flashlight – black		
S5D036	5 D cell flashlight - red		
S6D016	6 D cell flashlight - black		
S6D036	6 D cell flashlight - red		
ASXD026	Card of 2, Maglite D cell universal		
ASADUZU	mounting brackets		
ASXC046	C cell plain leather belt holder		
ASXD036	D cell plain leather belt holder		
ASXX07B	C or D cell red traffic wand		
ASXX08B	C or D cell yellow traffic wand		
ASXX09B	C or D cell white traffic wand		
	D cell accessory pack with red,		
ASXX376	clear, and blue lenses, anti-roll		
ASAASTO	device, two universal mounting		
	brackets and screws		
LWSA501	Card of 2, 5 D cell White Star bulbs		







ASXC046 ASXD026





# ML150LR LED RECHARGEABLE SYSTEM

•Lifetime tough® anodized aluminum body •QuickFocus™ switches from spot to flood in about 1/4 turn of the head •QuickClik® electronic switching to select from 5 operating modes with a userfriendly interface •Customizable for quick access to each user's preferred functions which includes high, low, eco, 12 Hz strobe, and momentary on/off •Advanced heat sink improves brightness and power management •Lithium Iron Phosphate (LiFePO4) chemistry for improved safety and performance and up to 2,000 charge/discharge cycles •Charging cradle fully charges the dead battery in 2.5 hours and cannot overcharge the battery •Cradle securely clamps light even in rough conditions •Includes: AC and DC adapters, charging cradle, and rechargeable battery Part No. ML150LR-1019.



Conso	IPX4 Winter Resistant

					ı
Function Set	General	Outdoor	Law Enforcement	Tactical	į
1 Click	Full Power	Full Power	Momentary	Momentary	Į
2 Clicks	Low Power	Low Power	Full Power	Full Power	_
3 Clicks	Eco	Strobe	Eco	Strobe	1

Specifications			
Lumens	1,082		
Beam Distance	458 m		
Drop Resistance	1 m		
Water Resistance	IPX4		
Peak Beam Intensity	52,555 cd		
Length	10.687"		
Head Diameter	1.937"		
Barrel Diameter	1.187"		
Run Time, High/Low/Eco	3h15m/18h/79h		
Weight With Batteries	439 g		

## MAG CHARGER® LED RECHARGEABLE SYSTEM

With the familiar "QuickClik™" system users can, within the "General" function set, choose Full Power (643 Lumens); Low Power (148 Lumens); or Eco Mode - Featuring improved recharging efficiency and a super power saving mode that yields up to 66 lumens with greatly extended run-time. There are three additional function sets Outdoor, Law Enforcement, and Military each offering a different set of functions invoked in a different sequence, for quickest access to the functions the particular user prefers. The IMPROVED, faster-handling "Quick Focus™" system adjusts from spot to flood with about a 1/4 turn of the head. Specifications: •643 lumens •407 beam distance •1.5" barrel diameter •41400 cd peak beam intensity •NiHM battery included

•794 g weight with batteries •Water-resistant •1 metre drop resistance •12.812" length •Run Time, High/Low/Eco: 4 hrs./17 hrs./37 hrs. •2.25" head diameter

Part No.	Description	
RL1019	MAG CHARGER® LED Rechargeable Flashlight System - This Kit comes complete with Flashlight, Battery, Charging Cradle, 12V DC Adapter and 110V AC adapter	Water Resi
ΔΗΧΧΩ25	Charger	





MAG CHARGER® RECHARGEABLE FLASHLIGHT SYSTEM

ARXX195 Part No. Description ARXX195 | Mag Charger 120 volt converter

LR00001 Card of 1, Mag Charger halogen bulb

# ML50LX™ LED 2 & 3-CELL C FLASHLIGHTS

•With the familiar "QuickClik™" system users can, within the "General" function set, choose Full Power (maximum Lumens); Low Power (up to 113 Lumens; 2-Cell or up to 105 Lumens; 3-Cell); or Eco Mode - a super power saving mode that yields up to 23 Lumens (2-Cell) or up to 20 lumens (2-Cell) with greatly extended run-time \*There are three additional function sets - Outdoor, Law Enforcement, and Military - each offering a different set of functions invoked in a different sequence, for quickest access to the functions the particular user prefers . The fast-handling "Quick Focus<sup>TM\*</sup> system adjusts from spot to flood with about a 1/4 turn of the head. Aggressive Knurled Design and Stealth Matte Finish \*Uses Alkaline batteries (not included) •1.2" barrel diameter •Water-resistant •1 metre drop resistance •1.977" head diameter •13" H x 5" W x 2" D blister size

Part No.	No. of Cells	Colour
ML50LX-S2CC6		Black
ML50LX-S2RI6		Green
ML50LX-S2RJ6	2	Grey
ML50LX-S2RK6		Tan
ML50LX-S2RN6		Red

ARXX175 12V DC Straight Wire AHXX065 120V AC Converter

Part No.	No. of Cells	Colour
ML50LX-S3CC6	3	Black
ML50LX-S3RI6		Green
ML50LX-S3RJ6		Grey

nead diameter 10 11 x 0 W x 2 D biloter size					
	Specifications:				
	No. of Cells	2	3		
	Lumens	490	611		
	Beam Distance	299 m	339 m		
	Weight With Batteries	360.61 g	453.59 g		
	Peak Beam Intensity	22400 cd	28760 cd		
	Length	8.184"	10.154"		
	Run Time, High/Low/Eco	15h/29h/112h	16h/42h/153h		



