

NSYMR86

Monobloc perforated plates H800xW600mm
with universal perforations 11x26mm.



Main

Range	Mounting accessories
Category	Mounting Plate
Application	Multi-purpose
Mounting plate description	Telequick perforated
Mounting location	Step slide Direct fixing on backstuds
Material	Steel
Surface finish	Zinc coated
For enclosure nominal dimensions	H: 800 mm W: 600 mm
Product compatibility	S3D, CRN, S3X, PLM, S57 enclosures
Quantity per set	Set of 1

Complementary

Fixing mode	Screwed on backstuds - screw type M8 By fixing element
Adjustment	Pitch 12.5 mm for on step slides, type NSYSDCR*
Height	750 mm
Width	551 mm
Depth	15 mm
Surface and useful surface	40.7 mm ²
Thickness	2 mm
Product weight	3.2 kg
Number of slots	867
Variant particularity	With enclosures H800 x W1200 Installation in rear of enclosure
Cut-out dimensions	11 x 26 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.