




Part Number: MMPSA 240/100 (Old Part Number MPS4452S)

Proximity Switch - Reed Switch based - Rectangular - Normally Open Contacts

Suggested Magnet: MMPSM

Product Data Sheet



APPLICATIONS INCLUDE

- Position and limit sensing.
- Linear actuators.
- Security system switch.
- Door Switch.

OPTIONS

- Colour: Standard = Blue housing / Grey wire. Also available Black housing / Black wire.
- Cable Entry: Standard = Right hand entry (shown above). Also available Left hand entry.
- Custom cable lengths, strip lengths, cable types, terminations.
- If you do not see what you need, jusk ask, as there is a strong possibility we can do it!

SPECIFICATION		
Contact Form / Style	Normally Open	
Switching Capacity (Resistive)	10 W/VA Max.	
Switching Voltage	400 VAC Max.	
Switching Current	0.5 A. Max.	
Carry Current	1.0 A. Max.	
Breakdown Voltage	600 VDC Min.	
Contact Resitance	150 mOhms Max.	
Switching Distance	10 mm Min.	
Operating Temperature Range	-20°C +85°C	
Storage temperature	-25°C +90°C	
Case Material	Blue Nylon 66	
Cable	2 x Round 0.14mm ² PVC covered Grey and insulated Brown / White	

REV. NO.	REVISION NOTE	DATE	SIGNATURE
A	Website	Feb 21, 2008	LG

TAKE A LOOK AT OUR VARIETY OF PRODUCTS

















As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.